

Çelik Hasır

Welded Wire Mesh



Q Tipleri (Q=Square) Kare Gözlü Çelik Hasırlar

| HASIRIN | | HASIR ÇUBUKLARININ | | | | | | | | AĞIRLIK | |
|----------|-----------|--------------------|-----|-------|------|-----------|--------|-------------|------|---------|-------|
| Tipi | Boy/Eni | ARALIĞI | | ÇAPI | | ÇIKINTISI | | KESİT ALANI | | m2 | Hasır |
| | m | Boy | En | Boy | En | Boy | En | Boy | En | | |
| | | mm | | cm2/m | | kg | | | | | |
| Q131/131 | 5,00/2,15 | 150 | 150 | 5,0 | 5,0 | 100/100 | 25/175 | 1,31 | 1,31 | 2,06 | 21,71 |
| Q158/158 | | 150 | 150 | 5,5 | 5,5 | 100/100 | 25/175 | 1,58 | 1,58 | 2,48 | 26,36 |
| Q188/188 | | 150 | 150 | 6,0 | 6,0 | 100/100 | 25/175 | 1,88 | 1,88 | 2,96 | 31,29 |
| Q221/221 | | 150 | 150 | 6,5 | 6,5 | 100/100 | 25/175 | 2,21 | 2,21 | 3,48 | 36,65 |
| Q257/257 | | 150 | 150 | 7,0 | 7,0 | 100/100 | 25/175 | 2,57 | 2,57 | 4,02 | 42,57 |
| Q295/295 | | 150 | 150 | 7,5 | 7,5 | 100/100 | 25/175 | 2,95 | 2,95 | 4,62 | 48,91 |
| Q317/188 | | 150 | 150 | 5,5d | 6,0 | 100/100 | 25/175 | 3,17 | 1,88 | 3,97 | 41,93 |
| Q317/188 | | 150 | 150 | 7,8 | 6,0 | 100/100 | 25/175 | 3,17 | 1,88 | 3,97 | 41,93 |
| Q317/317 | | 150 | 150 | 7,8 | 7,8 | 100/100 | 25/175 | 3,17 | 3,17 | 5,00 | 52,71 |
| Q335/335 | | 150 | 150 | 8,0 | 8,0 | 100/100 | 25/175 | 3,35 | 3,35 | 5,26 | 55,68 |
| Q377/188 | | 150 | 150 | 6,0d | 6,0 | 100/100 | 25/175 | 3,77 | 1,88 | 4,44 | 46,90 |
| Q377/188 | | 150 | 150 | 8,5 | 6,0 | 100/100 | 25/175 | 3,77 | 1,88 | 4,44 | 46,90 |
| Q377/377 | | 150 | 150 | 8,5 | 8,5 | 100/100 | 25/175 | 3,77 | 3,77 | 5,94 | 62,72 |
| Q424/424 | | 150 | 150 | 9,0 | 9,0 | 100/100 | 25/175 | 4,24 | 4,24 | 6,67 | 70,33 |
| Q443/221 | | 150 | 150 | 6,5d | 6,5 | 100/100 | 25/175 | 4,43 | 2,21 | 5,21 | 54,85 |
| Q443/221 | | 150 | 150 | 9,19 | 6,5 | 100/100 | 25/175 | 4,43 | 2,21 | 5,21 | 54,92 |
| Q443/443 | | 150 | 75 | 6,5d | 6,5 | 100/100 | 25/175 | 4,43 | 4,43 | 6,94 | 72,74 |
| Q443/443 | | 150 | 150 | 9,19 | 9,19 | 100/100 | 25/175 | 4,43 | 4,23 | 6,94 | 73,43 |
| Q513/513 | | 150 | 75 | 7,0d | 7,0 | 100/100 | 25/175 | 5,13 | 5,13 | 8,04 | 84,48 |
| Q513/513 | | 150 | 150 | 9,89 | 9,89 | 100/100 | 25/175 | 5,13 | 5,13 | 8,06 | 85,13 |

| | | | | | | | | | | | |
|----------|--|-----|-----|-------|-------|---------|--------|------|------|------|-------|
| Q524/524 | | 150 | 150 | 10,0 | 10,0 | 100/100 | 25/175 | 5,24 | 5,24 | 8,22 | 86,97 |
| Q589/378 | | 150 | 150 | 7,5d | 8,5 | 100/100 | 25/175 | 5,89 | 3,78 | 7,59 | 80,15 |
| Q589/378 | | 150 | 150 | 10,60 | 8,5 | 100/100 | 25/175 | 5,89 | 3,78 | 7,59 | 80,08 |
| Q589/589 | | 150 | 150 | 10,60 | 10,60 | 100/100 | 25/175 | 5,89 | 5,89 | 9,24 | 97,68 |
| Q589/589 | | 150 | 75 | 7,5d | 7,5 | 100/100 | 25/175 | 5,89 | 5,89 | 9,24 | 97,07 |

R Tipleri (R=Rectangle) Dikdörtgen Gözlü Çelik Hasır

| Hasırın | | Hasır Çubuklarının | | | | | | | | Ağırlık | |
|---------|-----------|--------------------|------|-------|---------|-----------|--------|-------------|------|---------|-------|
| Tipi | Boy/eni | Aralığı | | Çapı | | Çıkıntısı | | Kesit alanı | | m2 | Hasır |
| | | Boy | En | Boy | En | Boy | En | Boy | En | | |
| | m | mm | | | | | | cm2/m | | kg | |
| R 131 | 5,00/2,15 | 150 | 250 | 5,0 | 5,0 | 125/125 | 25/175 | 1,31 | 0,78 | 1,65 | 17,40 |
| R 158 | | 150 | 250 | 5,5 | 5,5 | 125/125 | 25/175 | 1,58 | 0,78 | 1,86 | 19,71 |
| R 188 | | 150 | 250 | 6,0 | 5,0 | 125/125 | 25/175 | 1,88 | 0,78 | 2,10 | 22,16 |
| R 221 | | 150 | 250 | 6,5 | 5,0 | 125/125 | 25/175 | 2,21 | 0,78 | 2,36 | 24,82 |
| R 257 | | 150 | 250 | 7,0 | 5,0 | 125/125 | 25/175 | 2,57 | 0,78 | 2,63 | 27,76 |
| R 295 | | 150 | 250 | 7,5 | 5,0 | 125/125 | 25/175 | 2,95 | 0,78 | 2,93 | 30,91 |
| R 317 | | 150 | 250 | 5,5d | 5,0 | 125/125 | 25/175 | 3,17 | 0,78 | 3,11 | 32,80 |
| R 317 | | 150 | 250 | 7,8 | 5,0 | 125/125 | 25/175 | 3,17 | 0,78 | 3,11 | 32,80 |
| R 335 | | 150 | 250 | 8,0 | 5,0 | 125/125 | 25/175 | 3,35 | 0,78 | 3,25 | 34,27 |
| R 377 | | 150 | 250 | 6,0d | 5,0 | 125/125 | 25/175 | 3,77 | 0,78 | 3,58 | 37,77 |
| R 377 | | 150 | 250 | 8,5 | 5,0 | 125/125 | 25/175 | 3,77 | 0,78 | 3,58 | 37,77 |
| R 443 | | 150 | 250 | 6,5d | 5,5 | 125/125 | 25/175 | 4,43 | 0,95 | 4,22 | 44,44 |
| R 443 | | 150 | 250 | 9,19 | 5,5 | 125/125 | 25/175 | 4,43 | 0,95 | 4,22 | 44,51 |
| R 513 | | 150 | 250 | 9,89 | 6 | 125/125 | 25/175 | 5,13 | 1,13 | 4,91 | 51,83 |
| R 513 | | 150 | 250 | 7,0d | 6,0 | 125/125 | 25/175 | 5,13 | 1,13 | 4,92 | 51,83 |
| R 524 | | 150 | 250 | 10 | 6,0 | 125/125 | 25/175 | 5,24 | 1,13 | 5,00 | 52,74 |
| R 589 | | 150 | 250 | 10,60 | 6,5 | 125/125 | 25/175 | 5,89 | 1,33 | 5,66 | 59,69 |
| R 589 | 150 | 250 | 7,5d | 6,5 | 125/125 | 25/175 | 5,89 | 1,33 | 5,66 | 59,76 | |

Tr Ters R Tipleri (R=Rectangle) Yana Yatık Dikdörtgen Gözlü Çelik Hasır

| TR Hasırın | | Hasır çubuklarının | | | | | | | | Ağırlık | |
|------------|-----------|--------------------|-----|------|-----|-----------|-------|-------------|------|---------|-------|
| Tipi | Boy/eni | Aralığı | | Çapı | | Çıkıntısı | | Kesit alanı | | m2 | Hasır |
| | | Boy | En | Boy | En | Boy | En | Boy | En | | |
| | m | mm | | | | | | cm2/m | | kg | |
| TR 131 | 5,00/2,15 | 300 | 150 | 5,0 | 5,0 | 125/125 | 25/25 | 0,65 | 1,31 | 1,59 | 17,09 |
| TR 158 | 5,00/2,15 | 300 | 150 | 5,0 | 5,5 | 125/125 | 25/25 | 0,65 | 1,58 | 1,81 | 19,43 |
| TR 188 | 5,00/2,15 | 300 | 150 | 5,0 | 6,0 | 125/125 | 25/25 | 0,65 | 1,88 | 2,04 | 21,91 |
| TR 221 | 5,00/2,15 | 300 | 150 | 5,0 | 6,5 | 125/125 | 25/25 | 0,65 | 2,21 | 2,29 | 24,61 |

| | | | | | | | | | | | |
|--------|-----------|-----|-----|------|-------|---------|-------|------|------|------|-------|
| TR 257 | 5,00/2,15 | 300 | 150 | 5,0 | 7,0 | 125/125 | 25/25 | 0,65 | 2,57 | 2,57 | 27,59 |
| TR 295 | 5,00/2,15 | 300 | 150 | 5,0 | 7,5 | 125/125 | 25/25 | 0,65 | 2,95 | 2,86 | 30,78 |
| TR 317 | 5,00/2,15 | 300 | 150 | 5,0 | 7,8 | 125/125 | 25/25 | 0,65 | 3,17 | 3,04 | 32,70 |
| TR 335 | 5,00/2,15 | 300 | 150 | 5,0 | 8,0 | 125/125 | 25/25 | 0,65 | 3,35 | 3,18 | 34,19 |
| TR 377 | 5,00/2,15 | 300 | 150 | 5,0 | 8,5 | 125/125 | 25/25 | 0,65 | 3,77 | 3,51 | 37,73 |
| TR 443 | 5,00/2,15 | 300 | 150 | 5,50 | 9,19 | 125/125 | 25/25 | 0,78 | 4,43 | 4,13 | 44,44 |
| TR 513 | 5,00/2,15 | 300 | 150 | 6,00 | 9,89 | 125/125 | 25/25 | 0,94 | 5,13 | 4,81 | 51,73 |
| TR 524 | 5,00/2,15 | 300 | 150 | 6,00 | 10,00 | 125/125 | 25/25 | 0,94 | 5,24 | 4,9 | 52,66 |
| TR 589 | 5,00/2,15 | 300 | 150 | 6,50 | 10,60 | 125/125 | 25/25 | 1,11 | 5,89 | 5,54 | 59,57 |

DEMCO DEMİR ÇELİK

Merkez

Mustafa Kemal Mah. 575 Sk. İlgin 4 Apt. No:16
D.1 K.1 Iskenderun HATAY/TURKEY

Tel : +90 326 618 27 77
Fax : +90 326 618 45 45
E-mail : info@demco.com.tr
Web : www.demco.com.tr

Fabrika

Yıldırım Beyazıt Mh. O. Colak Cd. No. 128 Payas
- HATAY/TURKEY

Tel : +90 326 755 92 01
Fax : +90 326 755 92 02