

SICAK HADDELENMİŞ RULO

- Commercial
- API*
- HSLA
- Structural
- Pressure Vessel
- Corten Steel
- Chequered steel

API 5L Grade can be produced to cover both sour and non-sour applications:

Non-Sour	Gr. B, X42, X46, X52, X56, X60, X65, X70, X80
Sour	Gr. B, X42, X46, X52, X60, X65

Mevcut Çap / Boyutlar

Nex Diskled	Thickness (mm)		Width (mm)		Inner Dia (mm)
Non- Pickled	From	То	From	То	
Hot Rolled Coil Mill Edge	1.2	17.5	850	1650	762
Hot Rolled Coil Non Skin Pass	4	6	850	1650	610
Hot Rolled Coil Trim Edge	1.5	8	850	1600	762
Hot Rolled Slit Coil	1.5	8	75	800	762

Pickled	Thickness (mm)		Width (mm)		Inner Dia (mm)
	From	То	From	То	
Hot Rolled Coil	1.5	6	850	1650	762
Hot Rolled Trimmed Coil	1.5	6	820	1600	762

Others	Thickness (mm)		Width (mm)		Inner Dia (mm)
	From	То	From	То	
Hot Rolled Skin Pass Coil	1.2	4	850	1600	762/610
Hot Rolled Chequered Coil	1.6	8	850	1500	762

SOĞUK HADDELENMİŞ RULO

Özellikler

Full Hard

High hardness, low tensile strength and ductility.

Annealed

As cold rolled full hard coils are not suitable for most applications due to high hardness, ultimate tensile strength and low ductility, the coils are annealed to the recrystallization temperature in the Batch Annealing Facility (BAF) to improve the workability for various applications.

Tempered (Skinpass)

The surface roughness of Cold Rolled Coils and Cold Rolled Slit Coils is controlled by tempering.

DIMENSIONS / SIZES				
Product	Thickness (mm)	Width (mm)	Inner Dia. (mm)	Outer Dia. (mm)
Cold Rolled Coils	0.3 - 3	850-1650	610	1950
Cold Rolled Slit Coils	0.3 - 3	75/800	610	1950

DEMCO DEMİR ÇELİK

Merkez	<u>Fabrika</u>
Mustafa Kemal Mah. 575 Sk. Ilgin 4 Apt. No:16 D.1 K.1 Iskenderun HATAY/TURKEY	Yildirim Beyazit Mh. O. Colak Cd. No. 128 Payas - HATAY/TURKEY
Tel : +90 326 618 27 77 Fax : +90 326 618 45 45 E-mail : info@demco.com.tr Web : www.demco.com.tr	Tel : +90 326 755 92 01 Fax : +90 326 755 92 02